

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ARC SD4i(E) Part A

UFI: UKX3-2TYC-7455-NQ9N

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

ARC Polymer Composite. This is the resin component of two part system using ARC SD4i (Part B) and mixed to provide chemical protection for storage tanks.

Uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	DK-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
Contact person:	eu-sds@chesterton.com	Telephone: +49 89 99 65 46 - 0
e-mail:	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315
Eye Irrit. 2; H319
Skin Sens. 1; H317
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)

Signal word: Warning

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 2 of 17

Pictograms:



Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
--------	--

2.3. Other hazards

The safety and health hazards are detailed separately for Part A and Part B. The final cured material is considered nonhazardous. Upon machining, refer to the precautions in the safety data sheets for Part A and Part B.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 3 of 17

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane			20 - < 25 %
	701-263-0		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411			
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)			15 - < 20 %
	500-033-5	603-074-00-8	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
13463-67-7	titanium dioxide			1 - < 5 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
9003-36-5	701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	20 - < 25 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
25068-38-6	500-033-5	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	15 - < 20 %
	Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100		
13463-67-7	236-675-5	titanium dioxide	1 - < 5 %
	oral: LD50 = > 2000 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 4 of 17

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let 1 glass of water be drunk in little sips (dilution effect).

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin and eye irritation.

Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- alcohol resistant foam
- Water spray jet
- Carbon dioxide (CO₂)
- Dry extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

- Carbon monoxide
- Carbon dioxide

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings.

In case of fire: Wear self-contained breathing apparatus.

Special protective equipment for firefighters: Protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Dispose of waste according to applicable legislation.

Use water spray jet to protect personnel and to cool endangered containers.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 5 of 17

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

- Avoid contact with skin, eyes and clothes.
- Take off contaminated clothing and wash it before reuse.
- Safe handling: see section 7
- Personal protection equipment: see section 8

6.2. Environmental precautions

- Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

6.3. Methods and material for containment and cleaning up

For containment

- Take up mechanically, placing in appropriate containers for disposal. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Personal protection equipment: see section 8
- Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. When using do not eat, drink or smoke.
- Avoid dust formation. Do not breathe dust.

Advice on general occupational hygiene

- Work in well-ventilated zones or use proper respiratory protection. Avoid contact with skin, eyes and clothes.
- Use protective skin cream before handling the product. Remove contaminated, saturated clothing immediately.
- When using do not eat, drink, smoke, sniff. Wash hands and face before breaks and after work and take a shower if necessary.

Further information on handling

- Wash hands before breaks and after work. Only wear fitting, comfortable and clean protective clothing. Used working clothes should not be worn outside the work area. Street clothing should be stored separately from work clothing.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

Hints on joint storage

- Keep away from:
 - Food and feedingstuffs

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 6 of 17

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
409-21-2	Silicon carbide, respirable dust	-	3		TWA (8 h)	
13463-67-7	Titanium dioxide, respirable dust	-	4		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 7 of 17

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
409-21-2	Silicon carbide			
	Worker DNEL, acute	inhalation	systemic	94 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	23 mg/m ³
	Consumer DNEL, acute	dermal	systemic	200 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	13 mg/kg bw/day
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane			
	Worker DNEL, long-term	inhalation	systemic	29,39 mg/m ³
	Worker DNEL, long-term	dermal	systemic	104,15 mg/kg bw/day
	Worker DNEL, long-term	inhalation	local	0,0083 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	8,7 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	62,5 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	6,25 mg/kg bw/day
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)			
	Worker DNEL, long-term	inhalation	systemic	12,25 mg/m ³
	Worker DNEL, acute	inhalation	systemic	12,25 mg/m ³
	Worker DNEL, long-term	dermal	systemic	8,33 mg/kg bw/day
	Worker DNEL, acute	dermal	systemic	8,33 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	3,571 mg/kg bw/day
	Consumer DNEL, acute	dermal	systemic	3,571 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,75 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	0,75 mg/kg bw/day
13463-67-7	titanium dioxide			
	Worker DNEL, long-term	inhalation	local	1,25 mg/m ³
	Consumer DNEL, long-term	oral	systemic	700 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 8 of 17

PNEC values

CAS No	Substance	
	Environmental compartment	Value
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	
	Freshwater	0,003 mg/l
	Freshwater (intermittent releases)	0,025 mg/l
	Marine water	0 mg/l
	Freshwater sediment	0,294 mg/kg
	Marine sediment	0,029 mg/kg
	Micro-organisms in sewage treatment plants (STP)	10 mg/l
	Soil	0,237 mg/kg
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	
	Freshwater	0,006 mg/l
	Marine water	0,001 mg/l
	Freshwater sediment	0,996 mg/kg
	Marine sediment	0,1 mg/kg
	Secondary poisoning	11 mg/kg
	Soil	0,196 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. Avoid dust formation. Knock down dust with water spray jet.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

- Eye glasses with side protection
- goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374

NBR (Nitrile rubber),

Wearing time with permanent contact: Thickness of the glove material: >= 0,4 mm, Breakthrough time: >480 min

Wearing time with occasional contact (splashes): Thickness of the glove material: >= 0,1 mm, Breakthrough time: > 30 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 9 of 17

Skin protection

Chemical protection clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Use suitable breathing apparatus.

Thermal hazards

No data available

Environmental exposure controls

Section 6: Accidental Release Measures

Section 12: Ecological Information (non-mandatory)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: viscous
Colour: grey / blue

Test method

Melting point/freezing point: No data available

Boiling point or initial boiling point and boiling range: No data available

Flammability

Solid/liquid: No data available

Flash point: > 200 °C

Decomposition temperature: No data available

pH-Value: not applicable

Water solubility: practically insoluble

Solubility in other solvents

No information available.

Density: 1,89 g/cm³

Relative vapour density: > 1 (Air=1)

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature

Solid: No data available

Gas: No data available

Oxidizing properties

No information available.

Other safety characteristics

Evaporation rate: < 1 (Ether=1)

Viscosity / dynamic: 110.000 mPa·s
(at 25 °C)

Further Information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 10 of 17

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Information is given in subsection 10.3., 10.5

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

- Strong acid
- Strong alkali
- Oxidising agent, strong
- Chlorine
- Oxygen

10.6. Hazardous decomposition products

- Hazardous decomposition products
- Carbon monoxide,
 - aldehydes,
 - Gases/vapours, toxic.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (inhalation dust/mist) 3613,334 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 11 of 17

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402
13463-67-7	titanium dioxide				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1996)	OECD Guideline 401

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane; epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-A-(epichlorhydrin))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 12 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy) methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (1998) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1,8	72 h	Raphidocelis subcapitata	Study report (1993) OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1998) OECD Guideline 202
	Crustacea toxicity	NOEC	0,3 mg/l	21 d	Daphnia magna	Study report (1984) OECD Guideline 211
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)					
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Pseudokirchneriella subcapitata	Study report (2007) OECD Guideline 201
	Crustacea toxicity	NOEC	0,3 mg/l	21 d	Daphnia magna	Study report (1984) OECD Guideline 211
13463-67-7	titanium dioxide					
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Carassius auratus	REACH Registration Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 50	72 h	Raphidocelis subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Artemia salina	REACH Registration Dossier OECD Guideline 202
	Fish toxicity	NOEC mg/l	>= 80	6 d	Danio rerio	REACH Registration Dossier OECD TG 210
	Algae toxicity	NOEC mg/l	>= 1	32 d	Synedra ulna, Scenedesmus quadricauda, Stigeocloni	Environ. Tox. Chem. 31, 2414-2422 (2012) In this study, the authors report the re
	Crustacea toxicity	NOEC	> 1 mg/l	10 d	Chironomus riparius	REACH Registration Dossier other: OECD Guideline 219
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	activated sludge, domestic	REACH Registration Dossier OECD Guideline 209

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 13 of 17

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	2,7
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	>= 2,64

BCF

CAS No	Chemical name	BCF	Species	Source
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	150		Other company data (
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	31		Study report (2010)
13463-67-7	titanium dioxide	> 0,47 - < 3,19	Artemia salina	REACH Registration D

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3082

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 14 of 17

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(epoxy resin)

14.3. Transport hazard class(es): 9

14.4. Packing group: III

Hazard label: 9

Classification code: M6

Special Provisions: 274 335 375 601

Limited quantity: 5 L

Excepted quantity: E1

Transport category: 3

Hazard No: 90

Tunnel restriction code: -

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(epoxy resin)

14.3. Transport hazard class(es): 9

14.4. Packing group: III

Hazard label: 9

Classification code: M6

Special Provisions: 274 335 375 601

Limited quantity: 5 L

Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(epoxy resin)

14.3. Transport hazard class(es): 9

14.4. Packing group: III

Hazard label: 9

Special Provisions: 274, 335, 969

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(epoxy resin)

14.3. Transport hazard class(es): 9

14.4. Packing group: III

Hazard label: 9

Special Provisions: A97 A158 A197 A215

Limited quantity Passenger: 30 kg G

Passenger LQ: Y964

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 15 of 17

Excepted quantity:	E1	
IATA-packing instructions - Passenger:		964
IATA-max. quantity - Passenger:		450 L
IATA-packing instructions - Cargo:		964
IATA-max. quantity - Cargo:		450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	(epoxy resin)

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-

(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-

[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)

titanium dioxide

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,12,14,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 16 of 17

IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC SD4i(E) Part A

Revision date: 03.01.2023

Page 17 of 17

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)