

# 276(E)



## ELECTRONIC COMPONENT CLEANER

### Description

Chesterton® 276(E) Electronic Component Cleaner is a fast acting, industrial strength cleaner containing zero ozone depleting potential. It is a high performance, non-chlorinated product designed to penetrate oils, greases and other soils common to industrial production areas.

Chesterton 276(E) offers a more environmentally responsible alternative to cleaners containing chlorinated solvents which can last for years in the atmosphere and cause damage to the vital layer of ozone protecting the earth.

Chesterton 276(E) Electronic Component Cleaner is formulated to be extremely low in residue and to dry quickly, preventing costly downtime. It is compatible with most surfaces and will require few process modifications other than normal precautions necessary for handling a flammable liquid.

Chesterton 276(E) should be used as received and applied by spray, brush or dipping. The strong flushing action provided in the aerosol gives additional mechanical break-up action to rid surfaces of dust, dirt and grime.

### Composition

Chesterton 276(E) Electronic Component Cleaner contains no chlorofluorocarbons or other chlorinated solvents that deplete the ozone layer.

Because it is formulated with an ultra-clean blend of solvents, Chesterton 276(E) will leave virtually no residue. It has a kauri-butanol value very similar to chlorofluorocarbons and will provide a similar degree of solvency.

### Suggested Uses

#### Spray Cleaning Of:

- Switches
- Controllers
- Panel Meters
- Circuit Boards
- Contacts
- Levers
- Control Panels

### Typical Physical Properties

Form	Liquid
Appearance	Clear, Transparent
Solubility in Water	Negligible
Flash Point, Pensky Martens ASTM D 93-85	-6°C
Aromatic Content (C8+) Weight %	Less than 0.2
Percent Volatile by Volume at 25°C	100
Color Saybolt ASTM D 156	> 30
Evaporation Rate at 25°C n-Butyl Acetate = 1	5 (approximate)
Vapor Pressure at 25°C ASTM D 2879	< 60 mm Hg
Density	0,7 kg/l
Specific Gravity	0.7
Dielectric Strength ASTM D 877	≤ 35 Kv

### Hard Surface Degreasing Of:

- Equipment
- Motors
- Non-Energized Electrical Equipment
- Parts In Process

### Features

- No Ozone Depleting Chemicals
- Fast Evaporation Rate
- Safe For Use On All Metals
- Low Aromatic Content
- Removes Dust, Dirt, Oil and Other Industrial Soils
- Low Residue
- NSF K2 Registration number 156048 (bulk) and 156047 (aerosol)

### Directions

Chesterton® 276(E) Electronic Component Cleaner should be used as received and not be diluted with other organic solvents or water.

Before using on painted surfaces, plastic or rubber, a small amount of 276(E) should be placed on the surface in a non-critical area. Wait about 15 minutes and check the surface for attack or softening. If damage has occurred, do not use product.

### Storage

Chesterton® 276(E) Electronic Component Cleaner should be stored at temperatures below 38°C and away from potential ignition sources. The product shelf life is two years from date of manufacture in unopened containers.

### Safety

Before using product, review the Material Safety Data Sheet (MSDS) or the appropriate safety sheet for your area.

Technical Data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W. CHESTERTON COMPANY DISCLAIMS ALL WARRANTIES EXPRESSED, OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE OR USE. LIABILITY, IF ANY, IS LIMITED TO PRODUCT REPLACEMENT ONLY.



DISTRIBUTED BY:

Chesterton International GmbH  
Am Lenzenfleck 23, DE-85737 Ismaning, Germany  
Tel +49-5223-96276(E)-0  
www.chesterton.com eu-pds@chesterton.com

© 2017 A.W. Chesterton Company  
® Registered trademark owned and licensed by  
A.W. Chesterton Company in USA and other countries,  
unless otherwise noted.