

SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200, WHMIS 2022 and Safe Work Australia

Revision date: 23 January 2025 **Date of previous issue:** 18 August 2021 **SDS No.** 392A-8

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

ARC SD4i (Part A) (BLU and GY), ARC SD4i RC (Part A) (BLU)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: ARC Polymer Composite. This is the resin component of a two part system using ARC SD4i (Part B) and mixed to provide chemical protection for storage tanks.

Uses advised against: No information available

Reason why uses advised against: Not applicable

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY
 860 Salem Street
 Groveland, MA 01834-1507, USA
 Tel. +1 978-469-6446
 (Mon. - Fri. 8:30 - 5:00 PM EST)
 SDS requests: www.chesterton.com
 E-mail (SDS questions): ProductSDSs@chesterton.com
 E-mail: customer.service@chesterton.com

Supplier:

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,
 Unit 105, Burlington, Ontario L7L 4X8 – Tel. 905-335-5055

1.4. Emergency telephone number

24 hours per day, 7 days per week
 Call Infotrac: 1-800-535-5053
 Outside N. America: +1 352-323-3500 (collect)
 NSW Poisons Information Centre (Australia): 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to 29 CFR 1910.1200 / WHMIS 2022 / Safe Work Australia / GHS

Skin irritation, Category 2, H315
 Skin sensitization, Category 1, H317
 Hazardous to the aquatic environment, Chronic, Category 2, H411

2.1.2. Additional information

For full text of H-statements: see SECTION 2.2.

2.2. Label elements

Labeling according to 29 CFR 1910.1200 / WHMIS 2022 / Safe Work Australia / GHS

Hazard pictograms:



Signal word:

Warning

Hazard statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements:	P261	Avoid breathing mist/vapours.
	P264	Wash skin thoroughly after handling.
	P272	Contaminated work clothing must not be allowed out of the workplace.
	P273	Avoid release to the environment.
	P280	Wear protective gloves.
	P302/352	IF ON SKIN: Wash with plenty of soap and water.
	P333/313	If skin irritation or rash occurs: Get medical advice/attention.
	P362/364	Take off contaminated clothing and wash it before reuse.
	P391	Collect spillage.
	P501	Dispose of contents/container to an approved waste disposal plant.

Supplemental information: None

2.3. Other hazards

The safety and health hazards are detailed separately for Part A and Part B. The final cured material is considered nonhazardous. Upon machining, refer to the precautions in the safety data sheets for Part A and Part B.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Hazardous Ingredients ¹	% Wt.	CAS No.	GHS Classification
Epoxy resin (number average molecular weight <= 700)	20-30	9003-36-5 *	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Other ingredients:

Silicon carbide	50-60	409-21-2	Not classified**
Titanium dioxide	1-5	13463-67-7	Not classified ^a **

For full text of H-statements: see SECTIONS 2.2 and 16.

*Alternative CAS No: 28064-14-4.

**Substance with a workplace exposure limit.

^a Contains less than 1 % of particles with aerodynamic diameter ≤ 10 µm.

¹ Classified according to: 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), WHMIS 2022, Safe Work Australia, GHS

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation:	Remove to fresh air. If not breathing, administer artificial respiration. Contact physician.
Skin contact:	Remove contaminated clothing. Wash clothing before reuse. Wash skin with soap and water. Consult physician.
Eye contact:	Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists.
Ingestion:	Wash out mouth with water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Contact physician immediately.
Protection of first-aiders:	No action shall be taken involving any personal risk or without suitable training. Avoid contact with the product while providing aid to the victim. See section 8.2.2 for recommendations on personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Moderate skin irritant. May cause skin sensitization as evidenced by rashes or hives.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: FIRE-FIGHTING MEASURES**5.1. Extinguishing media**

Suitable extinguishing media: Carbon dioxide, dry chemical, foam or water spray

Unsuitable extinguishing media: None known

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon monoxide, carbon dioxide.

Other hazards: Do not allow runoff from firefighting to enter drains or water courses.

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Australian HAZCHEM Emergency Action Code: 2 Z

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin contact. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Scoop up and transfer to a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Remove contaminated clothing immediately. Wash clothing before reuse. Contaminated leather including shoes cannot be decontaminated and should be discarded. Contaminated work clothing must not be allowed out of the workplace. After handling, wash before eating, drinking or smoking. Avoid breathing mist/vapours. Avoid creating and breathing dust during removal, drilling, grinding, sawing or sanding. Utilize exposure controls and personal protection as specified in Section 8.

7.2. Conditions for safe storage, including any incompatibilities

Keep container closed when not in use. Store between 10°C (50°F) and 32°C (90°F) in a dry area.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL ¹		ACGIH TLV ²		AUSTRALIA ES ³	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Epoxy resin (number average molecular weight <= 700)	N/A	N/A	N/A	N/A	N/A	N/A
Silicon carbide	(total)	15	(total)	10	N/A	10
	(resp.)	5	(resp.)	3		
Titanium dioxide	N/A	15	N/A	10	N/A	10

¹ United States Occupational Health & Safety Administration permissible exposure limits

² American Conference of Governmental Industrial Hygienists threshold limit values

³ Safe Work Australia, Workplace Exposure Standards for Airborne Contaminants

Biological limit values

No biological exposure limits noted for the ingredient(s).

8.2. Exposure controls**8.2.1. Engineering measures**

Good general mechanical ventilation and/or local exhaust. If it is necessary to alter the final cured product such that dust may be generated, use adequate dust extraction or damp down.

8.2.2. Individual protection measures

Respiratory protection: During spraying, wear suitable respiratory equipment.

Protective gloves: Chemical resistant gloves (e.g., nitrile rubber, butyl rubber, neoprene, PVC)

Eye and face protection: Safety goggles.

Other: Impervious clothing as necessary to prevent skin contact.

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	viscous liquid	pH	not applicable
Colour	gray	Kinematic viscosity	58,201 cSt @ 25°C
Odour	not applicable	Solubility in water	insoluble
Odour threshold	not determined	Partition coefficient	not applicable
		n-octanol/water (log value)	
Boiling point or range	not determined	Vapour pressure @ 20°C	not determined
Melting point/freezing point	not determined	Density and/or relative density	1.89 kg/l
% Volatile (by volume)	none	Weight per volume	15.7 lbs/gal.
Flammability	not determined	Vapour density (air=1)	> 1
Lower/upper flammability or explosion limits	not determined	Rate of evaporation (ether=1)	< 1
Flash point	> 200°C (> 392°F)	% Aromatics by weight	not determined
Method	PM Closed Cup	Particle characteristics	not applicable
Autoignition temperature	not determined	Explosive properties	not determined
Decomposition temperature	not determined	Oxidising properties	not determined

9.2. Other information

VOC (EPA 24): 0.016 lbs/gal (0.0019 kg/l). Dynamic viscosity: 110,000 cPs @ 25°C.

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Elevated temperatures.

10.5. Incompatible materials

Strong acids, bases and strong oxidizers like liquid Chlorine and concentrated Oxygen.

10.6. Hazardous decomposition products

Carbon Monoxide, Carbon Dioxide, aldehydes and other toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Primary route of exposure under normal use: Skin and eye contact. Personnel with pre-existing skin and eye disorders and skin allergies may be aggravated by exposure.

Acute toxicity -

Oral:

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Epoxy resin (number average molecular weight <= 700)	LD50, rat	> 5,000 mg/kg
Titanium dioxide	LD50, rat	> 10,000 mg/kg
Silicon carbide	NOAEL, rat	2,000 mg/kg

Dermal:

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Epoxy resin (number average molecular weight <= 700)	LD50, rabbit	> 2,000 mg/kg
Titanium dioxide	LD50, rabbit	> 10,000 mg/kg
Silicon carbide	NOAEL, rat	2,000 mg/kg

Inhalation:

Substance	Test	Result
Titanium dioxide	LC50, rat, 4 hours	> 6.82 mg/l (dust)

Skin corrosion/irritation:

Causes skin irritation.

Substance	Test	Result
Epoxy resin (number average molecular weight <= 700)	Skin irritation, rabbit	Moderate irritation
Titanium dioxide	Skin irritation, rabbit	Not irritating

Serious eye damage/irritation:

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Epoxy resin (number average molecular weight <= 700)	Eye irritation, rabbit	Not irritating
Titanium dioxide	Eye irritation, rabbit	Not irritating

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

Substance	Test	Result
Epoxy resin (number average molecular weight <= 700)	Skin sensitization, guinea pig	Sensitizing
Titanium dioxide	Skin sensitization, guinea pig	Not sensitizing

Germ cell mutagenicity:

Epoxy resin (number average molecular weight <= 700), Titanium dioxide: based on available data, the classification criteria are not met.

Carcinogenicity:

Epoxy resin (number average molecular weight <= 700): based on available data, the classification criteria are not met. The International Agency for Research on Cancer (IARC) has designated inhaled titanium dioxide as possibly carcinogenic to humans (group 2B). The titanium dioxide and silicon carbide in this product do not separate from the mixture or in of themselves become airborne, therefore, do not present a hazard in normal use.

Reproductive toxicity:

Epoxy resin (number average molecular weight <= 700), Titanium dioxide: based on available data, the classification criteria are not met.

STOT – single exposure:

Epoxy resin (number average molecular weight <= 700), Titanium dioxide: based on available data, the classification criteria are not met.

STOT – repeated exposure:

Epoxy resin (number average molecular weight <= 700), Titanium dioxide: based on available data, the classification criteria are not met.

Substance	Test	Result
Epoxy resin (number average molecular weight <= 700)	Sub-chronic NOAEL, oral, 90 days, rat, male / female (OECD 408)	250 mg/kg bw/day

Aspiration hazard:

Based on available data, the classification criteria are not met.

Other information:

None

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Epoxy resin (number average molecular weight ≤ 700) is toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment (LC50/EC50 between 1 and 10 mg/l in the most sensitive species; chronic NOEC, 21 days, Daphnia magna (OECD 211) 0.3 mg/l).

12.2. Persistence and degradability

Epoxy resin (number average molecular weight ≤ 700): not readily biodegradable (5% biodegradation, OECD 301F, 28 days). Titanium dioxide, Silicon carbide: inorganic substances.

12.3. Bioaccumulative potential

Epoxy resin (number average molecular weight ≤ 700): bioconcentration factor = 31 - 150 (QSAR), log Kow = 2.64 - 3.78, low potential for bioaccumulation.

12.4. Mobility in soil

Viscous liquid. Insoluble in water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Epoxy resin: if product enters soil, it will be mobile and may contaminate groundwater (log Koc ≤ 3.65).

12.5. Endocrine disrupting properties

None known

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Combine resin and curative. The final cured material is considered nonhazardous. Unreacted components are a special waste. Landfill sealed containers with stabilized and solidified liquids with a properly licensed facility. May be incinerated at an appropriate facility. Check local, state and national/federal regulations and comply with the most stringent requirement.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number or ID number**

ADG/ADR/RID/ADN/IMDG/ICAO: UN3082
 TDG: UN3082
 US DOT: UN3082

14.2. UN proper shipping name

ADG/ADR/RID/ADN/IMDG/ICAO: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
 TDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
 US DOT: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

14.3. Transport hazard class(es)

ADG/ADR/RID/ADN/IMDG/ICAO: 9
 TDG: 9
 US DOT: 9

14.4. Packing group

ADG/ADR/RID/ADN/IMDG/ICAO: III
 TDG: III
 US DOT: III

14.5. Environmental hazards

MARINE POLLUTANT

14.6. Special precautions for user

NO SPECIAL PRECAUTIONS FOR USER

14.7. Maritime transport in bulk according to IMO instruments

NOT APPLICABLE

14.8. Other information

US DOT: ERG NO.171,
 MAY BE SHIPPED AS NON-RESTRICTED IN NON-BULK PACKAGINGS (119 GALLONS OR LESS) BY MOTOR VEHICLE, RAIL CAR OR AIRCRAFT.
 (49 CFR 171.4(C))
 IMDG: EMS. F-A, S-F
 MAY BE SHIPPED AS NON-RESTRICTED IN SINGLE OR COMBINATION PACKAGINGS CONTAINING A NET QUANTITY PER SINGLE OR INNER PACKAGING OF 5 L OR LESS. (IMDG CODE AMENDMENT 37-14, 2.10.2.7)

ICAO/IATA: MAY BE SHIPPED AS NON-RESTRICTED IN SINGLE OR COMBINATION PACKAGINGS CONTAINING A NET QUANTITY PER SINGLE OR INNER PACKAGING OF 5 L OR LESS.(IATA DANGEROUS GOODS REGULATION 56TH EDITION, 4.4 SPECIAL PROVISIONS A197)

ADR: CLASSIFICATION CODE M6, TRANSPORT CATEGORY 3, TUNNEL RESTRICTION CODE (-)

MAY BE SHIPPED AS NON-RESTRICTED IN SINGLE OR COMBINATION PACKAGINGS CONTAINING A NET QUANTITY PER SINGLE OR INNER PACKAGING OF 5 L OR LESS. (ADR 2015 VOLUME 1, CHAPTER 3.3 SPECIAL PROVISIONS 375)

ADG HAZCHEM CODE: ●3Z **HIN:** 90

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. National regulations

US EPA SARA TITLE III

312 Hazards:

Chemicals subject to reporting requirements of Section 313 of EPCRA and of 40 CFR 372:

Skin irritation

None

Skin sensitization

TSCA: All components are listed or exempted.

Other national regulations: None

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms:

- ADG: Australian Dangerous Goods Code
- ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE: Acute Toxicity Estimate
- BCF: Bioconcentration Factor
- cATpE: Converted Acute Toxicity point Estimate
- ES: Exposure Standard
- GHS: Globally Harmonized System
- ICAO: International Civil Aviation Organization
- IMDG: International Maritime Dangerous Goods
- LC50: Lethal Concentration to 50 % of a test population
- LD50: Lethal Dose to 50% of a test population
- LOEL: Lowest Observed Effect Level
- N/A: Not Applicable
- NA: Not Available
- NOEC: No Observed Effect Concentration
- NOEL: No Observed Effect Level
- OECD: Organization for Economic Co-operation and Development
- (Q)SAR: Quantitative Structure-Activity Relationship
- REL: Recommended Exposure Limit
- RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
- SDS: Safety Data Sheet
- STEL: Short Term Exposure Limit
- STOT RE: Specific Target Organ Toxicity, Repeated Exposure
- STOT SE: Specific Target Organ Toxicity, Single Exposure
- TDG: Transportation of Dangerous Goods (Canada)
- TWA: Time Weighted Average
- US DOT: United States Department of Transportation
- WHMIS: Workplace Hazardous Materials Information System

Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data:

- Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)
- Chemical Classification and Information Database (CCID)
- European Chemicals Agency (ECHA) - Information on Chemicals
- Hazardous Chemical Information System (HCIS)
- National Institute of Technology and Evaluation (NITE)
- U.S. National Library of Medicine Toxicology Data Network (TOXNET)

Procedure used to derive the classification for mixtures according to GHS:

Classification	Classification procedure
Skin Irrit. 2, H315	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Relevant H-statements: H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H411: Toxic to aquatic life with long lasting effects.

Hazard pictogram names: Exclamation mark, environment

Further information: None

Date of last revision: 23 January 2025

Changes to the SDS in this revision: Complete change to represent new formulation.

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.