

according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

274 Industrial Degreaser (Aerosol)

UFI:

VM12-MWA2-05K5-0VFS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Petroleum base cleaner. Dissolves grease, oil, tar and other similar water insoluble soils generally encountered in the industrial and marine environments.

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	D-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
E-mail:	eu-sds@chesterton.com	
Contact person:	eu-sds@chesterton.com	Telephone: +49 89 99 65 46 - 0
E-mail:	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	
1.4. Emergency telephone	+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)	

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229 Compressed gas; H280 Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

 Hazard components for labelling

 Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha

 Signal word:
 Danger



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
Precautionary state	nents
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe gas.
P262	Do not get in eyes, on skin, or on clothing.
P301+P310	IF SWALLOWED: Immediately call a doctor.
P331	Do NOT induce vomiting.
P403	Store in a well-ventilated place.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

EUH066

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Page 2 of 14



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Page 3 of 14

Relevant ingredients

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No 1272/2008)				
64742-48-9	Naphtha (petroleum), hydro	otreated heavy; Low boiling point l	nydrogen treated naphtha	85 - < 90 %		
	265-150-3	649-327-00-6	01-2119486659-16			
	Asp. Tox. 1; H304					
106-97-8	butane			5 - 10 %		
	203-448-7	601-004-00-0				
	Flam. Gas 1; H220	·	·			
74-98-6	propane			5 - 10 %		
	200-827-9	601-003-00-5	01-2119486944-21			
	Flam. Gas 1; H220					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
64742-48-9	265-150-3	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	85 - < 90 %
	inhalation: LC5 mg/kg	0 = > 4,96 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000	
106-97-8	203-448-7	butane	5 - 10 %
	inhalation: LC5	0 = 273000 ppm (gases)	

Further Information

zu CAS 64742-48-9: contains less than 0,1 % w/w Benzene

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

After contact with eyes

Protect uninjured eye. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Page 4 of 14

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let 1 glass of water be drunken in little sips (dilution effect).

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Causes eye irritation. Causes skin irritation. Repeated exposure may cause skin dryness or cracking. Most important symptoms and effects, both acute and delayed: Headache, Dizziness, Pulmonary oedema Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- alcohol resistant foam
- Water spray jet
- Carbon dioxide (CO2)
- Dry extinguishing powder

Unsuitable extinguishing media

- Full water jet

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting.

Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings. In case of fire: Wear self-contained breathing apparatus.

Special protective equipment for firefighters: Protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Dispose of waste according to applicable legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Safe handling: see section 7 Personal protection equipment: see section 8



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Page 5 of 14

For non-emergency personnel

No information available.

For emergency responders

No information available.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe aerosol. Personal protection equipment: see section 8

Advice on protection against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Work in well-ventilated zones or use proper respiratory protection.

Wash hands before breaks and after work. Only wear fitting, comfortable and clean protective clothing. Used working clothes should not be worn outside the work area. Street clothing should be stored separately from work clothing.

Further information on handling

Observe instructions for use. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep cool. Protect from sunlight. Pressurised container: May burst if heated.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Revision No: 1,00

IRL - en



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Page 6 of 14

Further information on storage conditions

- Keep away from:
- Frost
- Heat
- Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
	Aliphatic hydrocarbon gases, Alkanes (C1-C3), Propane	-	-		Asphyxiant	
106-97-8	Butane, all isomers - n-butane	1000	-		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling poir	nt hydrogen treated napl	ntha	
Worker DNEL	, long-term	inhalation	systemic	1,9 mg/m³
Consumer DN	IEL, long-term	inhalation	systemic	0,41 mg/m³
Worker DNEL	, acute	inhalation	systemic	1286,4 mg/m ³
Worker DNEL	, long-term	inhalation	local	837,5 mg/m³
Worker DNEL	, acute	inhalation	local	1066,67 mg/m ³
Consumer DN	IEL, acute	inhalation	systemic	1152 mg/m ³
Consumer DN	IEL, long-term	inhalation	local	178,57 mg/m³
Consumer DN	IEL, acute	inhalation	local	640 mg/m ³

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

- Eye glasses with side protection
- goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Page 7 of 14

NBR (Nitrile rubber),

Wearing time with permanent contact: Thickness of the glove material: >= 0,4 mm, Breakthrough time: >480 min

Wearing time with occasional contact (splashes): Thickness of the glove material: >= 0,1 mm, Breakthrough time: > 30 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

Skin protection

For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Filtering device (full mask or mouthpiece) with filter: AX

Thermal hazards

No data available

Environmental exposure controls

No special measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid colourless		
Odour:	characteristic		
			Test method
Melting point/freezing point:		No data available	
Boiling point or initial boiling point and		188 °C	
boiling range:			
Flammability:		No data available	
Lower explosion limits:		No data available	
Upper explosion limits:		No data available	
Flash point:		> 61 °C	
Auto-ignition temperature:		227 °C	
Decomposition temperature:		No data available	
pH-Value:		not applicable	
Viscosity / kinematic:		No data available	
Water solubility:		Immiscible	
Solubility in other solvents			
No information available.			
Dissolution rate:		No data available	
Partition coefficient n-octanol/water:		No data available	
Dispersion stability:		No data available	

Revision No: 1,00



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024 Page 8 of 14 <1 hPa Vapour pressure: Vapour pressure: No data available Density: No data available Relative density: 0,77 kg/l Bulk density: No data available Relative vapour density: >1 (Air=1) 9.2. Other information Information with regard to physical hazard classes Explosive properties No information available. Self-ignition temperature Solid: No data available Gas: No data available Oxidizing properties No information available. Other safety characteristics Evaporation rate: <1 (n-butyl acetate = 1) No data available Sublimation point: Softening point: No data available Pour point: < -20 °C No data available Viscosity / dynamic: **Further Information**

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

This material is considered to be non-reactive under normal use conditions.

10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

- Nitrogen oxides (NOx),
- Carbon dioxide (CO2),



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Page 9 of 14

- Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64742-48-9	Naphtha (petroleum), hyd	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha						
	oral	LD50 mg/kg	> 5000	Rat	Study report (1986)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1986)	OECD Guideline 402		
	inhalation (4 h) vapour	LC50 mg/l	> 4,96	Rat	Study report (1992)	OECD Guideline 403		
106-97-8	butane							
	inhalation (4 h) gas	LC50 ppm	273000	Rat	GESTIS			

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Revision No: 1,00



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha							
	Acute fish toxicity	LL50	8,2 mg/l	96 h	Pimephales promelas	Study report (1995)	other: EPA 66013-75-009	
	Acute algae toxicity	ErC50	3,1 mg/l	72 h	Raphidocelis subcapitata	Study report (1995)	OECD Guideline 201	
	Acute crustacea toxicity	EL50	4,5 mg/l	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202	
	Fish toxicity	NOEC	2,6 mg/l	21 d	Daphnia magna	Study report (1999)	other: OECD Guideline 211	
	Crustacea toxicity	NOEC	2,6 mg/l	21 d	Daphnia magna	Study report (1999)	OECD Guideline 211	
106-97-8	butane							
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo	
	Acute algae toxicity	ErC50 mg/l	19,37	96 h		USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	
74-98-6	propane							
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo	
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Page 10 of 14



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Page 11 of 14

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
74-98-6	propane	1,09

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1

Revision No: 1,00

IRL - en



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Page 12 of 14

Revision date: 03.12.2024	
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity: Excepted quantity:	1 L E0
	E0
Marine transport (IMDG) <u>14.1. UN number or ID number:</u>	UN 1950
14.1. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	63, 190, 277, 327, 344, 381, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger: Passenger LQ:	30 kg G Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	No
14.6. Special precautions for user	
No information available.	
14.7. Maritime transport in bulk according to	o IMO instruments
No information available.	
SECTION 15: Regulatory information	
15.1. Safety, health and environmental regu	lations/legislation specific for the substance or mixture
EU regulatory information	
Restrictions on use (REACH, annex XVII):	
Entry 3, Entry 28, Entry 29, Entry 40	
National regulatory information	
Water hazard class (D):	2 - obviously hazardous to water
	2 - Openously hazardous to water

Revision No: 1,00

IRL - en



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Page 13 of 14

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: butane propane

SECTION 16: Other information

Abbreviations and acronyms

Flam. Gas: Flammable gases Aerosol: Aerosol Compressed gas Asp. Tox: Aspiration hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID:Règlement international conernat le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) CAS: Chemical Abstracts Service (division of the American Chemical Society) GHS: Globally Harmonized System of Classification and Labelling of Chemicals CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures, LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent EC50: Effectice concentration, 50 percent DNEL: Derived No Effect Level PNEC: Predicted No Effect Concentration PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Compressed gas; H280	
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
EUH066	Repeated exposure may cause skin dryness or cracking.



according to Regulation (EC) No 1907/2006

274 Industrial Degreaser (Aerosol)

Revision date: 03.12.2024

Page 14 of 14

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)