

according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

723 Sprasolvo®

UFI: HE8T-GKKN-3DPG-SE9F

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Penetrating oil – frees nuts, bolts, fittings without injury to base metal.

Uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Company name: Chesterton International GmbH

Street: Am Lenzenfleck 23

Place: D-85737 Ismaning GERMANY

Telephone: +49 89 99 65 46 - 0 Telefax: +49 89 99 65 46 - 50

E-mail: eu-sds@chesterton.com

Contact person: eu-sds@chesterton.com Telephone: +49 89 99 65 46 - 0

E-mail: eu-sds@chesterton.com
Internet: www.chesterton.com
Responsible Department: eu-sds@chesterton.com

1.4. Emergency telephone +49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 2; H223-H229 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy naphthenic

Distillates (petroleum), hydro-treated light; Kerosine - unspecified

Signal word: Warning



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 2 of 13

Pictograms:





Hazard statements

H223 Flammable aerosol.

H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing and eye protection/face protection.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 3 of 13

Relevant ingredients

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No	1272/2008)				
64742-52-5	Baseoil - unspecified, Distillates (pe	etroleum), hydrotreated heavy naphth	nenic	45 - 55 %		
	265-155-0	649-465-00-7	01-2119467170-45			
	Asp. Tox. 1; H304					
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified					
	265-149-8	649-422-00-2				
	Flam. Liq. 3, STOT SE 3, Asp. Tox	. 1, Aquatic Chronic 3; H226 H336 H	304 H412			
124-38-9	Carbon dioxide			1 - < 5 %		
	204-696-9					
	Compressed gas; H280					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc.	Limits, M-factors and ATE			
64742-52-5	265-155-0	Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy naphthenic	45 - 55 %		
	dermal: LD50	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg			
64742-47-8	265-149-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified	40 - 50 %		
	inhalation: LC50 = > 5,28 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000				
	lmg/kg				

Further Information

No information available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 4 of 13

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let 1 glass of water be drunken in little sips (dilution effect).

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Causes eye irritation.

Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

Most important symptoms and effects, both acute and delayed: Headache, Dizziness, Pulmonary oedema

Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- alcohol resistant foam
- Water spray jet
- Carbon dioxide (CO2)
- Dry extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting.

Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

 $\label{lem:co-ordinate} \mbox{ Co-ordinate fire-fighting measures to the fire surroundings.}$

In case of fire: Wear self-contained breathing apparatus.

Special protective equipment for firefighters: Protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Safe handling: see section 7

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 5 of 13

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Personal protection equipment: see section 8

Advice on protection against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothes. Use protective skin cream before handling the product. Remove contaminated, saturated clothing immediately. When using do not eat, drink, smoke, sniff. Wash hands and face before breaks and after work and take a shower if necessary.

Further information on handling

Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep cool. Protect from sunlight.

Pressurised container: May burst if heated.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Keep away from:

- Frost
- Heat
- Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 6 of 13

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
124-38-9	Carbon dioxide	5000	9000		TWA (8 h)	
		15000	27000		STEL (15 min)	

DNEL/DMEL values

	-					
CAS No	Substance					
DNEL type	DNEL type		Effect	Value		
64742-52-5	Baseoil - unspecified, Distillates (petroleum), hydrotreated I	neavy naphthenic				
Consumer DN	EL, long-term	inhalation	local	1,19 mg/m³		
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³		
Worker DNEL, long-term		inhalation	local	5,58 mg/m³		
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day		
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day		
64742-47-8	17-8 Distillates (petroleum), hydro-treated light; Kerosine - unspecified					
Consumer DNEL, long-term		oral	systemic	18,75 mg/kg bw/day		

PNEC values

CAS No	Substance			
Environmental compartment Value		Value		
64742-52-5 Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy naphthenic				
Secondary poisoning 9,33 mg/kg				

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

- Eye glasses with side protection
- goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374 NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material >= 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 7 of 13

Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))

Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))

Observe the wear time limits as specified by the manufacturer.

Skin protection

Wear suitable protective clothing.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Filtering device (full mask or mouthpiece) with filter: A-P2

Thermal hazards

No data available

Environmental exposure controls

No special measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: blue

Odour: like: Petroleum

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Flammability:
Lower explosion limits:
1,2
Upper explosion limits:
9,9
Flash point:
49 °C
Decomposition temperature:
No data available

Decomposition temperature:

pH-Value:

No data available

not applicable

Viscosity / kinematic:

< 121 mm²/s

(at 25 °C)

Water solubility: Immiscible

Solubility in other solvents

No information available.

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

(at 20 °C)

Density (at 20 °C): 0,83 g/cm³

Relative vapour density: > 1 (Air=1)

9.2. Other information

Information with regard to physical hazard classes



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 8 of 13

Explosive properties

Vapours can form explosive mixtures with air.

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No information available.

Other safety characteristics

Evaporation rate: <1 (Ether =1)

Sublimation point:No data availableSoftening point:No data availablePour point:No data available

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

This material is considered to be non-reactive under normal use conditions.

10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

10.5. Incompatible materials

- Oxidising agent

10.6. Hazardous decomposition products

- Carbon monoxide
- aldehydes
- Gases/vapours, toxic

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 9 of 13

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64742-52-5	Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy naphthenic						
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402	
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified						
	oral	LD50 mg/kg	> 5000	Rat	Study report (1992)	EPA OTS 798.1175	
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1992)	EPA OTS 798.1100	
	inhalation (4 h) vapour	LC50 mg/l	> 5,28	Rat	Study report (1987)	OECD Guideline 403	

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Distillates (petroleum), hydro-treated light; Kerosine - unspecified)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 10 of 13

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64742-52-5	Baseoil - unspecified, Dist	Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy naphthenic					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified						
	Acute fish toxicity	LL50 mg/l	2 - 5	96 h	Oncorhynchus mykiss	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50	8,3 mg/l		Raphidocelis subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EL50	1,4 mg/l	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202

12.2. Persistence and degradability

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
64742-52-5	Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy naphthenic					
	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	31%	28			

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Dispose of waste according to applicable legislation.

SECTION 14: Transport information



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 11 of 13

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 12 of 13

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

P3b FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy naphthenic

Distillates (petroleum), hydro-treated light; Kerosine - unspecified

Carbon dioxide

SECTION 16: Other information

Abbreviations and acronyms

Aerosol: Aerosol Compressed gas

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID:Règlement international conernat le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effectice concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative



according to Regulation (EC) No 1907/2006

723 Sprasolvo®

Revision date: 15.05.2024 Page 13 of 13

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 2; H223-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H223	Flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)