

SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200, WHMIS 2022 and Safe Work Australia

Revision date: 17 April 2025

Date of previous issue: 11 March 2025

SDS No. 175-27

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

723 Sprasolvo® (Aerosol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Penetrating oil - frees nuts, bolts, fittings without injury to base metal.

Uses advised against: No data available

Reason why uses advised against: Not applicable

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY

860 Salem Street

Groveland, MA 01834-1507, USA

Tel. +1 978-469-6446

(Mon. - Fri. 8:30 - 5:00 PM EST)

SDS requests: www.chesterton.com

E-mail (SDS questions): ProductSDSs@chesterton.com

E-mail: customer.service@chesterton.com

Supplier:

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,
Unit 105, Burlington, Ontario L7L 4X8 – Tel. 905-335-5055

1.4. Emergency telephone number

24 hours per day, 7 days per week

Call Infotrac: 1-800-535-5053

Outside N. America: +1 352-323-3500 (collect)

NSW Poisons Information Centre (Australia): 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to 29 CFR 1910.1200 / WHMIS 2022 / Safe Work Australia / GHS

Flammable aerosol, Category 2, H223, H229

Aspiration hazard, Category 1, H304

Skin irritation, Category 2, H315

Specific target organ toxicity – single exposure, Category 3, H336

Hazardous to the aquatic environment, Chronic, Category 3, H412

2.1.2. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16.

2.2. Label elements

Labeling according to 29 CFR 1910.1200 / WHMIS 2022 / Safe Work Australia / GHS

Hazard pictograms:



Signal word:

Danger

Hazard statements:	H223	Flammable aerosol.
	H229	Pressurized container: May burst if heated.
	H304	May be fatal if swallowed and enters airways.
	H316	Causes mild skin irritation.
	H336	May cause drowsiness or dizziness.
	H412	Harmful to aquatic life with long lasting effects.
Precautionary statements:	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P261	Avoid breathing vapours/spray.
	P271	Use only outdoors or in a well-ventilated area.
	P273	Avoid release to the environment.
	P280	Wear protective gloves.
	P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
	P331	Do NOT induce vomiting.
	P304/340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P312	Call a POISON CENTER or doctor if you feel unwell.
	P332/313	If skin irritation occurs: Get medical advice/attention.
	P403	Store in a well-ventilated place.
Supplemental information:	P410/412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501	Dispose of contents/container to an approved waste disposal plant.

Supplemental information: None

2.3. Other hazards

None known

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Hazardous Ingredients ¹	% Wt.	CAS No.	GHS Classification
Distillates (petroleum), hydrotreated heavy naphthenic*	45-55	64742-52-5	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light	40-50	64742-47-8	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 3, H316 STOT SE 3, H336 Aquatic Chronic 3, H412
Carbon dioxide	1-5	124-38-9	Press. Gas (Comp.), H280

*Contains less than 3 % DMSO extract as measured by IP 346.

For full text of H-statements: see SECTION 16.

¹ Classified according to: 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L.O. 111F), WHMIS 2022, Safe Work Australia, GHS

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation:	Remove to fresh air. If not breathing, administer artificial respiration. Contact physician immediately.
Skin contact:	Wash skin with soap and water. Take off contaminated clothing and wash it before reuse. Contact physician if irritation persists.
Eye contact:	Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists.
Ingestion:	Do not induce vomiting. Contact physician immediately.
Protection of first-aiders:	No action shall be taken involving any personal risk or without suitable training. Avoid contact with the product while providing aid to the victim. See section 8.2.2 for recommendations on personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Causes mild skin irritation. May cause mild eye irritation. High vapor concentrations cause eye and respiratory tract irritation and dizziness, headache and other central nervous system effects. Aspiration into the lungs may cause chemical pneumonitis or pulmonary oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: FIRE-FIGHTING MEASURES**5.1. Extinguishing media**

Suitable extinguishing media: Carbon dioxide, dry chemical, foam or water spray

Unsuitable extinguishing media: High volume water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon Monoxide, aldehydes and other toxic fumes.

Other hazards: Pressurized containers, when heated, are a potential explosive hazard.

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Australian HAZCHEM Emergency Action Code: 2 Y

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Contain spill to a small area. Keep away from sources of ignition - No smoking. If removal of ignition sources is not possible, then flush material away with water. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Shake well before using. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No Smoking. Vapors are heavier than air and will collect in low areas. Vapor accumulations could flash and/or explode if ignited. Utilize exposure controls and personal protection as specified in Section 8. After handling, wash before eating, drinking or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (120°F). Do not pierce or burn, even after use.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL ¹		ACGIH TLV ²		AUSTRALIA ES ³	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Oil mist, mineral	N/A	5	N/A	5 (inhal.)	N/A	5
Distillates (petroleum), hydrotreated light	500	N/A	212*	1200*	N/A	N/A
Carbon dioxide	5000	9000	5000	9000	5000	9000
			30000	STEL: 54000	STEL: 30000	54000

*Based on the procedure described in appendix H, "Reciprocal calculation method for Certain Refined Hydrocarbon Solvent Vapor Mixtures" of the ACGIH TLVs® and BEIs®.

¹ United States Occupational Health & Safety Administration permissible exposure limits

² American Conference of Governmental Industrial Hygienists threshold limit values

³ Safe Work Australia, Workplace Exposure Standards for Airborne Contaminants

Biological limit values

No biological exposure limits noted for the ingredient(s).

8.2. Exposure controls

8.2.1. Engineering measures

No special requirements. If exposure limits are exceeded, provide adequate ventilation. Vapors are heavier than air and will collect in low areas.

8.2.2. Individual protection measures

Respiratory protection: Not normally needed. If exposure limits are exceeded, use a half or full-face respirator with combined dust/organic vapour filter (e.g., EN filter type A/P2).

Protective gloves: Chemical resistant gloves (e.g., nitrile rubber, butyl rubber, neoprene, PVC)

Eye and face protection: Recommend safety glasses.

Other: None

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	liquid	pH	not applicable
Colour	blue	Kinematic viscosity	< 120 cSt @ 25°C
Odour	petroleum distillate odor	Solubility in water	negligible
Odour threshold	not determined	Partition coefficient	not applicable
		n-octanol/water (log value)	
Boiling point or range	not determined	Vapour pressure @ 20°C	not determined
Melting point/freezing point	not determined	Density and/or relative density	0.83 kg/l
% Volatile (by volume)	50%	Weight per volume	6.9 lbs/gal
Flammability	not determined	Vapour density (air=1)	> 1
Lower/upper flammability or explosion limits	LEL 1.2%, UEL 9.9%	Rate of evaporation (ether=1)	< 1
Flash point	49°C (120°F), product only	% Aromatics by weight	0.5%
Method	Tag Closed Cup	Particle characteristics	not applicable
Autoignition temperature	not determined	Explosive properties	not determined
Decomposition temperature	no data available	Oxidising properties	not determined

9.2. Other information

None

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Open flames and high temperatures.

10.5. Incompatible materials

Strong oxidizers like liquid Chlorine and concentrated Oxygen, reactive metals.

10.6. Hazardous decomposition products

Carbon Monoxide, aldehydes and other toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects****Primary route of exposure under normal use:**

Inhalation, skin and eye contact.

Information is based on available data on product components. Product as a whole has not been evaluated.

Acute toxicity -**Oral:**

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	LD50, rat	> 5000 mg/kg, estimated
Distillates (petroleum), hydrotreated light	LD50, rat	> 5000 mg/kg

Dermal:

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	LD50, rabbit	> 2000 mg/kg, estimated
Distillates (petroleum), hydrotreated light	LD50, rabbit	> 2000 mg/kg

Inhalation:

High vapor concentrations cause eye and respiratory tract irritation and dizziness, headache and other central nervous system effects.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	LC50, rat, 4 hours	> 5 mg/l, estimated
Distillates (petroleum), hydrotreated light	LC50, rat, 4 hours, vapour	> 5.28 mg/l (analytical)
Distillates (petroleum), hydrotreated light	LC50, rat, 4 hours, mist	> 5.2 mg/l

Skin corrosion/irritation:

Causes mild skin irritation.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	Skin irritation, rabbit	Not irritating
Distillates (petroleum), hydrotreated light	Skin irritation, rabbit	Not irritating; Slightly irritating; Moderate irritation

Serious eye damage/irritation:

Based on available data on components, the classification criteria are not met. Direct contact may cause mild eye irritation.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	Eye irritation, rabbit (OECD 405)	Not irritating
Distillates (petroleum), hydrotreated light	Eye irritation, rabbit	Not irritating; Slightly irritating

Respiratory or skin sensitisation:

Skin sensitization: Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated heavy naphthenic	Skin sensitization, guinea pig (OECD 406)	Not sensitizing
Distillates (petroleum), hydrotreated light	Skin sensitization, guinea pig	Not sensitizing

Germ cell mutagenicity:

Based on available data on components, the classification criteria are not met.

Carcinogenicity:

This product contains no carcinogens as listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the Occupational Safety and Health Administration (OSHA) or the European Chemicals Agency (ECHA).

Reproductive toxicity:	Based on available data on components, the classification criteria are not met.
STOT – single exposure:	May cause drowsiness or dizziness.
STOT – repeated exposure:	Based on available data on components, the classification criteria are not met.
Aspiration hazard:	Aspiration into the lungs may cause chemical pneumonitis or pulmonary oedema.
Other information:	None

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Mineral oil, biodegradation: 31% (OECD 301F, 28 days). Distillates (petroleum), hydrotreated light: can degrade in air; inherently biodegradable.

12.3. Bioaccumulative potential

Mineral oil: not expected to bioaccumulate. Distillates (petroleum), hydrotreated light, Octanol/water partition coefficient (log Kow): 2.1-5 (estimated).

12.4. Mobility in soil

Liquid. Insoluble in water. Floats on water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Distillates (petroleum), hydrotreated light: will rapidly evaporate to the air if released into the environment.

12.5. Endocrine disrupting properties

None known

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Incinerate absorbed material with a properly licensed facility. Incinerate pressurized containers at an approved facility. Check local, state and national/federal regulations and comply with the most stringent requirement.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number or ID number**

ADG/ADR/RID/ADN/IMDG/ICAO:	UN1950
TDG:	UN1950
US DOT:	UN1950

14.2. UN proper shipping name

ICAO:	AEROSOLS, FLAMMABLE
ADG/IMDG:	AEROSOLS
ADR/RID/ADN:	AEROSOLS, <i>FLAMMABLE</i>
TDG:	AEROSOLS, <i>FLAMMABLE</i>
US DOT:	AEROSOLS, <i>FLAMMABLE</i>

14.3. Transport hazard class(es)

ADG/ADR/RID/ADN/IMDG/ICAO:	2.1
TDG:	2.1
US DOT:	2.1

14.4. Packing group

ADG/ADR/RID/ADN/IMDG/ICAO:	NOT APPLICABLE
TDG:	NOT APPLICABLE
US DOT:	NOT APPLICABLE

14.5. Environmental hazards

NO ENVIRONMENTAL HAZARDS

14.6. Special precautions for user

NO SPECIAL PRECAUTIONS FOR USER

14.7. Maritime transport in bulk according to IMO instruments

NOT APPLICABLE

14.8. Other information

US DOT: SHIPPED AS LIMITED QUANTITY IN PACKAGING HAVING A RATED CAPACITY GROSS WEIGHT OF 66 LB. OR LESS (49 CFR 173.306(A),(3),(I)).

ERG NO. 126

IMDG: EMS. F-D, S-U, SHIPPED AS LIMITED QUANTITY

ADR: CLASSIFICATION CODE 5F, TRANSPORT CATEGORY 2, TUNNEL RESTRICTION CODE (E), SHIPPED AS LIMITED QUANTITY

ADG HAZCHEM CODE: N/A **HIN:** (1)

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. National regulations****US EPA SARA TITLE III****312 Hazards:**

Chemicals subject to reporting requirements of Section 313 of EPCRA and of 40 CFR 372:

Flammable aerosol

None

Gas under pressure

Aspiration hazard

Specific target organ toxicity – single exposure

TSCA: All chemical components are listed in the TSCA inventory.

Other national regulations: None

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms:

- ADG: Australian Dangerous Goods Code
- ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE: Acute Toxicity Estimate
- BCF: Bioconcentration Factor
- cATpE: Converted Acute Toxicity point Estimate
- ES: Exposure Standard
- GHS: Globally Harmonized System
- ICAO: International Civil Aviation Organization
- IMDG: International Maritime Dangerous Goods
- LC50: Lethal Concentration to 50 % of a test population
- LD50: Lethal Dose to 50% of a test population
- LOEL: Lowest Observed Effect Level
- N/A: Not Applicable
- NA: Not Available
- NOEC: No Observed Effect Concentration
- NOEL: No Observed Effect Level
- OECD: Organization for Economic Co-operation and Development
- (Q)SAR: Quantitative Structure-Activity Relationship
- REL: Recommended Exposure Limit
- RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
- SDS: Safety Data Sheet
- STEL: Short Term Exposure Limit
- STOT RE: Specific Target Organ Toxicity, Repeated Exposure
- STOT SE: Specific Target Organ Toxicity, Single Exposure
- TDG: Transportation of Dangerous Goods (Canada)
- TWA: Time Weighted Average
- US DOT: United States Department of Transportation
- WHMIS: Workplace Hazardous Materials Information System

Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data:

- Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)
- Chemical Classification and Information Database (CCID)
- European Chemicals Agency (ECHA) - Information on Chemicals
- Hazardous Chemical Information System (HCIS)
- National Institute of Technology and Evaluation (NITE)
- U.S. National Library of Medicine Toxicology Data Network (TOXNET)

Procedure used to derive the classification for mixtures according to GHS:

Classification	Classification procedure
Aerosol 2, H223, H229	On basis of test data
Asp. Tox, H304	On basis of components and spray pattern
Skin Irrit. 3, H316	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 3, H412	Calculation method

Relevant H-statements: H226: Flammable liquid and vapour.
H229: Pressurized container: May burst if heated.
H280: Contains gas under pressure; may explode if heated.
H304: May be fatal if swallowed and enters airways.
H316: Causes mild skin irritation.
H336: May cause drowsiness or dizziness.
H412: May cause long lasting harmful effects to aquatic life.

Hazard pictogram names: Flame, health hazard, exclamation mark

Further information: None

Date of last revision: 17 April 2025

Changes to the SDS in this revision: Product identifier.

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.