

### SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200, WHMIS 2022 and Safe Work Australia

Revision date: 29 January 2025 Date of previous issue: 27 April 2005 SDS No. 167F-5

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

723 FG Sprasolvo® (Bulk)

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Food grade mineral oil based lubricant. Penetrates and loosens rust, scale, corrosion, dirt,

graphite, etc., without injury to the basic metal, wood, paint or plastic.

Uses advised against: No information available
Reason why uses advised against: Not applicable
1.3. Details of the supplier of the safety data sheet

Company: Supplier:

A.W. CHESTERTON COMPANY

860 Salem Street

Groveland, MA 01834-1507, USA

Tel. +1 978-469-6446

(Mon. - Fri. 8:30 - 5:00 PM EST) SDS requests: www.chesterton.com

E-mail (SDS questions): ProductSDSs@chesterton.com

E-mail: customer.service@chesterton.com

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive, Unit 105, Burlington, Ontario L7L 4X8 – Tel. 905-335-5055

# 1.4. Emergency telephone number

24 hours per day, 7 days per week Call Infotrac: 1-800-535-5053

Outside N. America: +1 352-323-3500 (collect)
NSW Poisons Information Centre (Australia): 13 11 26

# **SECTION 2: HAZARDS IDENTIFICATION**

### 2.1. Classification of the substance or mixture

### 2.1.1. Classification according to 29 CFR 1910.1200 / WHMIS 2022 / Safe Work Australia / GHS

Flammable liquid, Category 4, H227 Aspiration hazard, Category 1, H304

### 2.1.2. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16.

#### 2.2. Label elements

Labeling according to 29 CFR 1910.1200 / WHMIS 2022 / Safe Work Australia / GHS

Hazard pictograms:

Signal word: Danger

Hazard statements: H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

Date: 29 January 2025 **SDS No.** 167F-5

sources. No smoking.

P280 Wear protective gloves and eye/face protection.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. P301/310

Do NOT induce vomiting. P331

In case of fire: Use water fog, foam, dry chemical or CO2 to extinguish. P370/378

Keep away from heat, hot surfaces, sparks, open flames and other ignition

P403 Store in a well-ventilated place.

P501 Dispose of contents/container to an approved waste disposal plant.

Supplemental information: None

**Precautionary statements:** 

P210

### 2.3. Other hazards

As with any organic solvent based product, care should be taken to avoid excessive inhalation of vapors. This is especially important in enclosed areas or areas with poor ventilation.

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

Hazardous Ingredients <sup>1</sup>	% Wt.	CAS No.	GHS Classification
White mineral oil (petroleum)	45-55	8042-47-5	Asp. Tox. 1, H304
Naphtha (petroleum), hydrotreated heavy*	45-55	64742-48-9	Flam. Liq. 4, H227 Asp. Tox. 1, H304

For full text of H-statements: see SECTION 16.

### **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

Inhalation: Remove to fresh air. If not breathing, administer artificial respiration. Contact physician.

Skin contact: Wash skin with soap and water. Contact physician if irritation persists.

Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists. Eye contact:

Do not induce vomiting. Contact physician immediately. Ingestion:

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. Do not ingest. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. See section

8.2.2 for recommendations on personal protective equipment.

### 4.2. Most important symptoms and effects, both acute and delayed

Direct eye contact may result in eye irritation. Vapor concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects. Aspiration into the lungs may cause chemical pneumonitis or pulmonary oedema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## **SECTION 5: FIRE-FIGHTING MEASURES**

### 5.1. Extinguishing media

Suitable extinguishing media: Dry chemical, carbon dioxide, 45fog, foam

Unsuitable extinguishing media: High volume water jet 5.2. Special hazards arising from the substance or mixture

**Hazardous combustion products:** Carbon Monoxide, Carbon Dioxide and other toxic fumes.

Other hazards: None 5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Australian HAZCHEM Emergency Action Code: 2 Z

<sup>\*</sup>Contains less than 0.1 % w/w Benzene.

<sup>&</sup>lt;sup>1</sup> Classified according to: 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), WHMIS 2022, Safe Work Australia, GHS

**Date:** 29 January 2025 SDS No. 167F-5

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

#### 6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

### 6.3. Methods and material for containment and cleaning up

Contain spill to a small area. Keep away from sources of ignition - No smoking. If removal of ignition sources is not possible, then flush material away with water. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

#### 6.4. Reference to other sections

Refer to section 13 for disposal advice.

#### **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Keep container closed when not in use. Vapors are heavier than air and will collect in low areas. Vapor accumulations could flash and/or explode if ignited. Utilize exposure controls and personal protection as specified in Section 8. After handling, wash before eating, drinking or smoking.

# 7.2. Conditions for safe storage, including any incompatibilities

Store in cool, dry area.

## 7.3. Specific end use(s)

No special precautions.

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### 8.1. Control parameters

#### Occupational exposure limit values

Ingredients	OSHA PEL1		ACGIH TLV <sup>2</sup>		AUSTRALIA ES <sup>3</sup>	
	ppm	mg/m³	ppm	mg/m³	ppm	mg/m³
Oil mist, mineral	N/A	5	N/A	5 (inhal.)	N/A	5
Naphtha (petroleum), hydrotreated heavy	N/A	N/A	171 *	1,200 *	N/A	N/A

### **Biological limit values**

No biological exposure limits noted for the ingredient(s).

#### 8.2. Exposure controls

### 8.2.1. Engineering measures

No special requirements. If exposure limits are exceeded, provide adequate ventilation.

### 8.2.2. Individual protection measures

Respiratory protection: Not normally needed. If exposure limits are exceeded, use a half or full-face respirator with

combined dust/organic vapour filter (EN filter type A/P2).

**Protective gloves:** Chemical resistant gloves (e.g., butyl rubber)

Eye and face protection: Safety goggles.

Other: Impervious clothing as necessary to prevent skin contact.

### 8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

<sup>\*</sup>Based on the procedure described in appendix H, "Reciprocal calculation method for Certain Refined Hydrocarbon Solvent Vapor Mixtures" of the ACGIH TLVs® and BEIs®.

<sup>&</sup>lt;sup>1</sup> United States Occupational Health & Safety Administration permissible exposure limits

<sup>&</sup>lt;sup>2</sup> American Conference of Governmental Industrial Hygienists threshold limit values

<sup>&</sup>lt;sup>3</sup> Safe Work Australia, Workplace Exposure Standards for Airborne Contaminants

**Date:** 29 January 2025 **SDS No.** 167F-5

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on basic physical and chemical properties

Physical statethin liquidpHnot applicableColourclearKinematic viscositynot determinedOdourpetroleum odorSolubility in waternegligibleOdour thresholdnot determinedPartition coefficient> 0

n-octanol/water (log value)

Boiling point or range not determined Vapour pressure @ 20°C not determined Density and/or relative density Melting point/freezing point not determined 0.83 kg/l % Volatile (by volume) 50% Weight per volume 6.93 lbs/gal. Vapour density (air=1) Flammability not determined > 1

Lower/upper flammability or explosion limits

not applicable

61°C (142°F)

PM Closed Cup

not determined

not determined

Rate of evaporation (ether=1) < 1

% Aromatics by weight < 0.01%
Particle characteristics not applicable
Explosive properties not determined
Oxidising properties not determined

9.2. Other information

**Autoignition temperature** 

**Decomposition temperature** 

None

#### **SECTION 10: STABILITY AND REACTIVITY**

#### 10.1. Reactivity

Flash point

Method

Refer to sections 10.3 and 10.5.

### 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

### 10.4. Conditions to avoid

Open flames, heat, sparks and red hot surfaces.

## 10.5. Incompatible materials

Strong oxidizers like liquid Chlorine and concentrated Oxygen.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

### 11.1. Information on toxicological effects

Primary route of exposure under normal use:

Inhalation, skin and eye contact. Personnel with pre-existing skin disorders and impaired lung function are generally aggravated by exposure.

Acute toxicity -

**Oral:** Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Naphtha (petroleum), hydrotreated	LD50, rat	> 10,000 mg/kg
heavy		
White mineral oil (petroleum)	LD50, rat	> 5,000 mg/kg

**Dermal:** Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Naphtha (petroleum), hydrotreated	LD50	> 3,160 mg/kg
heavy		
White mineral oil (petroleum)	LD50, rabbit	> 2,000 mg/kg

**Date:** 29 January 2025 SDS No. 167F-5

**Inhalation:** Vapor concentrations above recommended exposure levels are irritating to the eyes and the

respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects. Naphtha (petroleum), hydrotreated heavy: based on available

data, the classification criteria are not met.

SubstanceTestResultWhite mineral oil (petroleum)LC50, rat, 4 h, aerosol> 5 mg/l

Skin corrosion/irritation: Prolonged or repeated skin contact may defat the skin and cause skin irritation.

 Substance
 Test
 Result

 White mineral oil (petroleum)
 Skin irritation, rabbit
 Not irritating

Serious eye damage/ irritation: Naphtha (petroleum), hydrotreated heavy: May cause mild eye irritation; based on available data, the classification criteria are not met.

Substance Test Result
White mineral oil (petroleum) Eye irritation Not irritating

Respiratory or skin sensitisation:

Skin sensitization: Based on available data on components, the classification criteria are not

Substance	Test	Result
Naphtha (petroleum), hydrotreated	Skin sensitization,	Not sensitizing
heavy	guinea pig, read-across	
White mineral oil (petroleum)	Skin sensitization,	Not sensitizing
. ,	guinea pig	

Germ cell mutagenicity: Naphtha (petroleum), hydrotreated heavy, White mineral oil (petroleum): based on available

data, the classification criteria are not met.

Carcinogenicity: This product contains no carcinogens as listed by the National Toxicology Program (NTP), the

International Agency for Research on Cancer (IARC), the Occupational Safety and Health

Administration (OSHA) or the European Chemicals Agency (ECHA).

Reproductive toxicity: Naphtha (petroleum), hydrotreated heavy, White mineral oil (petroleum): based on available

data, the classification criteria are not met.

STOT – single exposure: Naphtha (petroleum), hydrotreated heavy: not expected to cause organ damage from a single

exposure. White mineral oil (petroleum): based on available data, the classification criteria are

not met.

STOT - repeated exposure: Naphtha (petroleum), hydrotreated heavy, White mineral oil (petroleum): based on available

data, the classification criteria are not met.

**Aspiration hazard:** Aspiration into the lungs may cause chemical pneumonitis or pulmonary oedema.

Other information: None

### **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

#### 12.1. Toxicity

Not expected to be harmful to aquatic organisms (LC50/EC50/ErC50 > 100 mg/l in the most sensitive species). Naphtha (petroleum), hydrotreated heavy: chronic NOEC, Daphnia magna = 1 mg/l.

### 12.2. Persistence and degradability

Naphtha (petroleum), hydrotreated heavy: expected to degrade rapidly in air; may biodegrade (ready biodegradability, water, 28 days: 31.3%, similar material). Mineral oil: this substance is not readily biodegradable to OECD criteria but is inherently biodegradable.

### 12.3. Bioaccumulative potential

Mineral oil: log Kow > 4.

# 12.4. Mobility in soil

Liquid. Solubility in water: negligible. Floats on water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Naphtha (petroleum), hydrotreated heavy: will rapidly evaporate to the air if released into the environment. Mineral oil: expected to exhibit low mobility in soil.

**Date:** 29 January 2025 SDS No. 167F-5

### 12.5. Endocrine disrupting properties

None known

### 12.6. Other adverse effects

None known

### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Incinerate absorbed material and/or containers with a properly licensed facility. Check local, state and national/federal regulations and comply with the most stringent requirement.

### **SECTION 14: TRANSPORT INFORMATION**

14.1. UN number or ID number

ADG/ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE TDG: NOT APPLICABLE US DOT: NOT APPLICABLE

14.2. UN proper shipping name

ADG/ADR/RID/ADN/IMDG/ICAO:

TDG:

NON-HAZARDOUS, NON REGULATED

NON-HAZARDOUS, NON REGULATED

NON-HAZARDOUS, NON REGULATED

14.3. Transport hazard class(es)

ADG/ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE NOT APPLICABLE US DOT: NOT APPLICABLE

14.4. Packing group

ADG/ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE TDG: NOT APPLICABLE US DOT: NOT APPLICABLE

14.5. Environmental hazards

**NOT APPLICABLE** 

14.6. Special precautions for user

**NOT APPLICABLE** 

14.7. Maritime transport in bulk according to IMO instruments

**NOT APPLICABLE** 

14.8. Other information

NOT APPLICABLE

# **SECTION 15: REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.1.1. National regulations

US EPA SARA TITLE III

312 Hazards: Chemicals subject to reporting requirements of Section 313 of

EPCRA and of 40 CFR 372:

Flammable liquid None Aspiration hazard

TSCA: All components are listed or exempted.

**Date:** 29 January 2025 SDS No. 167F-5

Other national regulations: None

# **SECTION 16: OTHER INFORMATION**

**Abbreviations** ADG: Australian Dangerous Goods Code

and acronyms: ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE: Acute Toxicity Estimate BCF: Bioconcentration Factor

cATpE: Converted Acute Toxicity point Estimate

ES: Exposure Standard

GHS: Globally Harmonized System

ICAO: International Civil Aviation Organization IMDG: International Maritime Dangerous Goods LC50: Lethal Concentration to 50 % of a test population

LD50: Lethal Dose to 50% of a test population

LOEL: Lowest Observed Effect Level

N/A: Not Applicable NA: Not Available

NOEC: No Observed Effect Concentration

NOEL: No Observed Effect Level

OECD: Organization for Economic Co-operation and Development

(Q)SAR: Quantitative Structure-Activity Relationship

REL: Recommended Exposure Limit

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

STOT RE: Specific Target Organ Toxicity, Repeated Exposure STOT SE: Specific Target Organ Toxicity, Single Exposure TDG: Transportation of Dangerous Goods (Canada)

TWA: Time Weighted Average

US DOT: United States Department of Transportation WHMIS: Workplace Hazardous Materials Information System

Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data:

Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST) Chemical Classification and Information Database (CCID)

European Chemicals Agency (ECHA) - Information on Chemicals

Hazardous Chemical Information System (HCIS) National Institute of Technology and Evaluation (NITE)

U.S. National Library of Medicine Toxicology Data Network (TOXNET)

### Procedure used to derive the classification for mixtures according to GHS:

Classification	Classification procedure
Flam. Liq. 4, H227	On basis of test data
Asp. Tox. 1, H304	Bridging principle "Dilution"

Relevant H-statements: H227: Combustible liquid.

H304: May be fatal if swallowed and enters airways.

Hazard pictogram names: Health hazard

Further information: None

Date of last revision: 29 January 2025

Changes to the SDS in this revision: Sections 1.1, 1.2, 1.3, 2.1, 2.2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16.

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.