

1830-SSP

Advanced Slurry Pump Packing for Maximum Performance

Hybrid Yarn Technology. Superior Sealing. Easier Maintenance.

When it comes to slurry sealing, you need a durable, high-performance packing that can withstand the toughest conditions while remaining easy to maintain. Chesterton® 1830-SSP delivers on all fronts with its innovative hybrid yarn construction for exceptional strength, flexibility, and longevity.

Why Choose Chesterton 1830-SSP?

- **Built for Tough Slurry Applications** – Engineered to handle abrasive and high-solids environments, making it the go-to choice for demanding industries.
- **Hybrid Yarn Construction** – Combines advanced graphite PTFE and carbon yarn reinforcement, providing superior sealing performance with enhanced durability.
- **Easier Removal, Less Downtime** – Designed for quick and easy repacking, reducing maintenance time and maximizing equipment uptime.
- **Versatile and Reliable** – Performs across a wide range of slurry applications, delivering consistent sealing and extended service life.

For a sealing solution that works as hard as your equipment, trust Chesterton 1830-SSP to reduce maintenance, improve reliability, and keep your operations running smoothly. Upgrade your slurry pump packing with Chesterton 1830-SSP. Stronger. Smarter. More Efficient.

Technical Data

Material	Carbon-reinforced, expanded PTFE with graphite
Size Low	8 mm (0.312")
Size High	25.4 mm (1")
Pressure Limit Rotating	28 bar g (400 psig)
Speed Max	18 m/s (3600 fpm)
Temperature Max	260°C (500°F)
Chemical Resistance (High)	14 pH
Chemical Resistance Notes	with exception of strong oxidizers in the 0 – 2 pH range



- Developed to meet rigid demands of slurry sealing applications
- Excellent chemical resistance
- Low friction, less heat generation, non-abrasive: saves shafts and shaft sleeves

1830-SSP Ordering Information				
Size		Packaged ± 10%		Item Number
mm	Inch	kg	lbs	
8.0	5/16	These sizes are available upon request.		
9.5	3/8	0.908	2	052605
		2.270	5	052606
		4.540	10	052607
10.0	–	0.908	2	052608
		2.270	5	052609
11.0	7/16	0.908	2	052610
		2.270	5	052611
12.0	–	0.908	2	052612
		2.270	5	052613
12.7	1/2	0.908	2	052614
		2.270	5	052615
		4.540	10	052616
14.0	9/16	2.270	5	052617
		4.540	10	052618
16.0	5/8	4.540	10	052619
17.5	11/16	4.540	10	052620
19.0	3/4	4.540	10	052621
20.0	–	4.540	10	052622
20.5	13/16	These sizes are available upon request.		
22.0	7/8	4.540	10	052624
24.0	15/16	These sizes are available upon request.		
25.4	1	4.540	10	052626

Applications

Bauxite slurries, bottom ash slurry pumps, mineral handling slurries, tailings pumps, and other slurry processing applications

Chesterton ISO certificates available on chesterton.com/corporate/iso

Distributed by:

Technical data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W. Chesterton Company disclaims all warranties express or implied, including warranties of merchantability and fitness for a particular purpose. Liability, if any, is limited to product replacement only. Any images contained herein are for general illustrative or aesthetic purposes only and are not intended to convey any instructional, safety, handling or usage information or advice respecting any product or equipment. Please refer to relevant Safety Data Sheets, Product Data Sheets, and/or Product Labels for safe use, storage, handling, and disposal of products, or consult with your local Chesterton sales representative.

© 2025 A.W. Chesterton Company.
 ® Registered trademark owned by A.W. Chesterton Company
 in USA and other countries, unless otherwise noted.