ARC HT-T (Part B)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022
Issue date: 2026-06-18 Revision date: 2026-06-18 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : ARC HT-T (Part B)
Product code : 434B-7a

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : ARC Polymer Composite to be mixed with ARC HT-T (Part A) to provide a corrosion resistant coating for hot water/steam environment.

1.4. Supplier's details

Supplier
A.W. Chesterton Company
860 Salem Street
Groveland, MA, 01834-1507
USA
T +1 978-469-6446 (Mon. - Fri. 8:30 - 5:00 PM EST) - F +1 978-469-6785
productsdss@chesterton.com - www.chesterton.com

Canada: A.W. Chesterton Company Ltd.
889 Fraser Drive, Unit 105
Burlington, ON, L7L 4X8
Canada
T 905-335-5055

1.5. Emergency phone number

Emergency number : 24 hours a day, 7 days a week
Call Infotrac: 1-800-535-5053
Outside North America: +1 352-323-3500 (collect call)

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Acute toxicity (oral), Category 3
Acute toxicity (inhalation:vapour), Category 4
Skin corrosion, Category 1B
Serious eye damage, Category 1

Skin sensitization, Category 1
Specific target organ toxicity, Repeated exposure, Category 2
Health hazards not otherwise classified, Category 1

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :

Signal word (GHS) : Danger

Hazard statements (GHS) : Toxic if swallowed
Causes severe skin burns and eye damage
May cause an allergic skin reaction
Harmful if inhaled
May cause damage to organs (kidneys, liver, muscle, stomach) through prolonged or repeated exposure (oral)
Causes severe damage to the respiratory tract

Precautionary statements (GHS) : Do not breathe dusts or mists.
Wash hands, forearms and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves, protective clothing, eye protection, face protection.

Call a POISON CENTER or doctor/physician if you feel unwell.
Wash contaminated clothing before reuse.If swallowed: Immediately call a poison center or doctor.
Rinse mouth.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If skin irritation or rash occurs: Get medical advice or attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Store locked up.
Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

97.96% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w) Weight*
Formaldehyde, polymer with benzenamine, hydrogenated	Formaldehyde, polymer with benzenamine, hydrogenated Copolymer of benzenamine and formaldehyde	CAS-No.: 135108-88-2	45 – 70
Cyclohexanamine, 4,4'-methylenebis-	Cyclohexanamine, 4,4'-methylenebis- Bis(cyclohexylamine)	CAS-No.: 1761-71-3	30 – 60
Diethylenetriamine	Diethylenetriamine Bis(2-aminoethyl)amine	CAS-No.: 111-40-0	1 – 5

*Chemical name, CAS number and /or exact concentration have been withheld as a trade secret

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell

First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Immediately call a POISON CENTER/doctor.

First-aid measures after skin contact : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : Harmful if inhaled. Causes severe damage to the respiratory tract. Causes burns to the respiratory system.

Symptoms/effects after skin contact : Causes severe skin burns. Symptoms may include redness, pain, blisters. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.

Symptoms/effects after ingestion : Toxic if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic symptoms : May cause damage to organs (kidneys, liver, muscle, stomach) through prolonged or repeated exposure (oral).

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2). Dry chemical. Alcohol resistant foam.

Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Ammonia. Toxic Nitrogen.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

For non-emergency personnel

Emergency procedures : Do not touch or walk on the spilled product.

For emergency responders

Environmental precautions : Prevent entry to sewers and public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leak if safe to do so. Absorb or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not get in eyes, on skin, or on clothing.Do not breathe dust, fume, gas, mist, spray, vapours. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place. Store locked up.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Diethylenetriamine (111-40-0)	
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	1 ppm
ACGIH® chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	4 mg/m³
NIOSH REL TWA	1 ppm
US-NIOSH chemical category	SK: SYS-DIR(COR)-SEN Oct 2020

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness. Examples of preferred glove barrier materials include: Neoprene. nitrile
Eye protection:
Wear eye/face protection
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment. Respirator with filter for organic vapor, (e.g., EN filter type A/P2).

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Liquid
Appearance	:	Viscous..
Colour	:	Blue
Odour	:	Amine
Odour threshold	:	No data available
pH	:	No data available
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	> 215 °C / >420°F
Flash point	:	> 100 °C / >212°F (Closed Cup)
Relative evaporation rate (ether=1)	:	< 1
Flammability (solid, gas)	:	Not flammable.
Vapour pressure	:	No data available
Relative vapour density at 20°C/ 68 °F	:	> 1
Relative density	:	1.019 kg/L
Solubility	:	Slightly soluble.
Partition coefficient n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	2400 cP (25°C)
Explosive limits	:	No data available
Particle characteristics	:	No data available

Formaldehyde, polymer with benzenamine, hydrogenated	
Boiling point	> 220 °C (at 1013 hPa)
Flash point	> 200 °C (closed cup)
Vapour pressure	0.055 Pa (at 20 °C)

Cyclohexanamine, 4,4'-methylenebis-	
Boiling point	320 °C Atm. press.: 760 mm Hg
Flash point	160 °C Atm. press.: 1013 hPa
Auto-ignition temperature	285 °C (at 1013 hPa)
Vapour pressure	0.0549 Pa Temp.: 20 °C

Diethylenetriamine	
Boiling point	207 °C (at 1013 hPa)
Flash point	96.7 °C (closed cup)
Auto-ignition temperature	398.9 °C
Vapour pressure	0.37 mm Hg (at 20 °C)

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : 0.6 lb/gal EPA 24

SECTION 10 Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Open flames. High temperature. Incompatible materials.

10.5. Incompatible materials

Minerals.Acids. Strong oxidizers (Chlorine, Oxygen).10.6. Hazardous decomposition products
May include, and are not limited to: oxides of carbon. ammonia. Toxic nitrogen.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Toxic if swallowed.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Inhalation:vapour: Harmful if inhaled.

ARC HT-T (Part B)	
ATE US (oral)	300 mg/kg bodyweight
ATE US (vapours)	11 mg/l/4h
Unknown acute toxicity	97.96% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

Formaldehyde, polymer with benzenamine, hydrogenated (135108-88-2)	
LD50 oral rat	50 – 300 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method)
LD50 dermal rabbit	> 1000 mg/kg (Source: ECHA_API)

Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)	
LD50 oral	380 mg/kg
LD50 dermal rabbit	2110 mg/kg bodyweight Animal: rabbit, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity)
LD50 dermal	2110 mg/kg

Diethylenetriamine (111-40-0)	
LD50 oral rat	1080 mg/kg (Source: JAPAN_GHS)
LD50 oral	1080 mg/kg
LD50 dermal rabbit	672 mg/kg (Source: JAPAN_GHS)
LD50 dermal	1040 mg/kg
LC50 inhalation rat	70 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns.

Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)	
pH	11.6 Temp.: 25 °C

Diethylenetriamine (111-40-0)	
pH	12 (conc: 100 g/L (DTA in water)

Serious eye damage/irritation : Causes serious eye damage.

Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)	
pH	11.6 Temp.: 25 °C

Diethylenetriamine (111-40-0)	
pH	12 (conc: 100 g/L (DTA in water)

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Not classified.

Reproductive toxicity : Not classified.

STOT-single exposure : Not classified.

STOT-repeated exposure : May cause damage to organs (kidneys, liver, muscle, stomach) through prolonged or repeated exposure (oral).

Formaldehyde, polymer with benzenamine, hydrogenated (135108-88-2)	
NOAEL (oral, rat, 90 days)	15 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)	
STOT-repeated exposure	May cause damage to organs (liver, muscle, stomach) through prolonged or repeated exposure.

Aspiration hazard : Not classified.

Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)	
Viscosity, kinematic	84.211 mm²/s

Symptoms/effects after inhalation : Harmful if inhaled. Causes severe damage to the respiratory tract. Causes burns to the respiratory system.

Symptoms/effects after skin contact : Causes severe skin burns. Symptoms may include redness, pain, blisters. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.

Symptoms/effects after ingestion : Toxic if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic symptoms : May cause damage to organs (kidneys, liver, muscle, stomach) through prolonged or repeated exposure (oral).

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified.

Hazardous to the aquatic environment, long–term (chronic) : Not classified.

Formaldehyde, polymer with benzenamine, hydrogenated (135108-88-2)	
LC50 - Fish [1]	63 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static] Source: ECHA)
EC50 - Crustacea [1]	15.4 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	43.94 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	7.07 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	68 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [2]	6.84 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	140 – 200 mg/l Test organisms (species):
EC50 72h - Algae [2]	141.42 – 200 mg/l Test organisms (species):
LOEC (chronic)	7.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1 mg/l Test organisms (species): other:freshwater fish

Diethylenetriamine (111-40-0)	
LC50 - Fish [1]	248 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static] Source: IUCLID)
EC50 - Crustacea [1]	16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	1014 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static] Source: EPA)
EC50 72h - Algae [1]	1164 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h - Algae [1]	345.6 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h - Algae [2]	592 mg/l (Species: Desmodesmus subspicatus)
NOEC chronic crustacea	5.6 mg/l

12.2. Persistence and degradability

ARC HT-T (Part B)	
Persistence and degradability	Not established.

Formaldehyde, polymer with benzenamine, hydrogenated (135108-88-2)	
Persistence and degradability	Rapidly degradable

Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)	
Persistence and degradability	Rapidly degradable

Diethylenetriamine (111-40-0)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

ARC HT-T (Part B)	
Bioaccumulative potential	Not established.

Formaldehyde, polymer with benzenamine, hydrogenated (135108-88-2)	
BCF - Fish [1]	(>18 - <22)
Partition coefficient n-octanol/water	2.68 (at 21 °C (at pH 12.5)

Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)	
Partition coefficient n-octanol/water	2.2 (at 23 °C (at pH 11)

Diethylenetriamine (111-40-0)	
BCF - Fish [1]	(>2.8 - <=6.3 (whole body w.w.)
Partition coefficient n-octanol/water	-1.3

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified.
Fluorinated greenhouse gases : No

Other information : No other effects known.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Combine resin and curative before disposal. Once fully cured, the material is considered non-hazardous and may be disposed of at a properly licensed landfill facility in sealed containers. Unreacted components are classified as special waste and may be incinerated at an appropriate facility.

SECTION 14 Transport information

In accordance with DOT / TDG

14.1. UN Number

UN-No. (DOT) : UN2735
UN-No. (TDG) : UN2735

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Amines, liquid, corrosive, n.o.s. (cycloaliphatic amine)
Proper Shipping Name (TDG) : AMINES, LIQUID, CORROSIVE, N.O.S. (cycloaliphatic amine)

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8

TDG
Transport hazard class(es) (TDG) : 8
Hazard labels (TDG) : 8

14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

DOT
UN-No. (DOT) : UN2735

DOT Special Provisions (49 CFR 172.102)	:	IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	154
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	203
DOT Packaging Bulk (49 CFR 173.xxx)	:	241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	60 L
DOT Vessel Stowage Location	:	A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	:	52 - Stow ‘‘separated from’’ acids

TDG

UN-No. (TDG)	:	UN2735
TDG Special Provisions	:	16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.
Explosive Limit and Limited Quantity Index	:	5 L
Excepted quantities (TDG)	:	E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	:	5 L
Emergency Response Guide (ERG) Number	:	153

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. State regulations

WARNING: This product can expose you to Diisononyl phthalate, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date	:	2026-06-18
Issue date	:	2026-06-18
Other information	:	None.
Prepared by	:	Nexreg Compliance Inc. www.Nexreg.com

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2026 B&W

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.